

CRT

RUNCO INTERNATIONAL
C R T T E C H N O L O G Y

DTV-992 ULTRA



HDTV

HIGH DEFINITION
FULLY COLOR CORRECTED AND FILTERED LENSES
EYE-Q™ AUTO-CONVERGENCE
RS-232 CONTROLLABLE



DTV-873



DTV-940



DTV-947



DTV-1200



The World's Finest Home Theater Products™

The DTV-992 ULTRA has all the features necessary for the true home theater experience. With its true 8-inch CRTs, fully color-corrected and filtered lenses, and accurate 25-point zone convergence system, this projector will precisely reproduce video from any source. Its scan rate capabilities and large CRTs make it the perfect choice for use with any High-Definition format, as well as any type of processor. Finally, this unit comes equipped with the Eye-Q™ auto-convergence system for easy touch-ups.

FEATURES

- 25 point zone convergence
- 230 ANSI lumens
- Color corrected and filtered HD-8 lenses
- Eye-Q™: The intelligent way to converge
- Impressive gamma correction
- RS232 controllable
- Multiple Aspect Ratios
- 110 KHz Horizontal scan rate
- 120 MHz Bandwidth
- Convergence on green for accurate linearity

SPECIFICATIONS

Scan Frequency:	Horizontal: 15-110 KHz Vertical: 37-200 Hz	Configurations:	Front or rear, floor, or ceiling mount
Optical Resolution:	10 line pairs/mm	Aspect Ratio:	Anamorphic, widescreen, 4:3
Video Standards:	NTSC, PAL, SECAM, NTSC 4.43	Contrast Ratio:	100:1
Bandwidth:	75 MHz (120 MHz 992 Ultra)	Convergence:	Dynamic geometry, 25 point zone
CRTs:	8" High performance with Electromagnetic focus	Power Requirements:	115 VAC, 50/60 Hz
Lenses:	Fully color corrected and filtered HD-8 lenses	Power Consumption:	500W
Inputs:	Component/RGB	Cabinet Dimensions:	Width: 23.25 in./590.55 mm Depth: 43 in./1092.20 mm Height: 14.25 in./361.95 mm Weight: 156 lbs./70.76 mm
Color Balance:	3200K, 5400K, 6500K, 9300K, Custom	Safety Regulations:	Complies with: FCC Class B, CE, C-Tick
Light Output:	1250 lumens/230 ANSI lumens	Storage:	10-122° F (-12-50°C)
Convergence Memories:	32	Operating Environment:	32-104° F (0-40°C)
Picture Size:	5-20 ft. wide	Humidity:	0-90%, non-condensing
Throw Distance:	1.33 x width (widescreens) 1.40 x width (4:3 screens)		

Call factory for more specific information on export specifications.
Specifications are subject to change without notice.



**THE WORLD'S FINEST
HOME THEATER PRODUCTS™**

Runco International®
2463 Tripaldi Way, Hayward CA 94545
Tel: 510-293-9154 • Fax: 510-293-0201
www.runco.com